

# 1064nm In-line Fiber Polarizer

## Product Features

- High Extinction Ratio
- Low Insertion Loss
- High Return Loss

## Product Applications

- Communication Systems
- Test Instrumentations
- Fiber Sensors
- Research

## Specifications

Parameter	Unit	Value
Center Wavelength	nm	1060
Operating Wavelength Range	nm	$\lambda \pm 30$
Typ. Insertion Loss at 23°C	dB	$\leq 0.4$
Max. Insertion Loss at 23°C	dB	$\leq 0.6$
Min. Return loss (input/output)	dB	$\geq 50/50$
Typ. Extinction ratio at 23°C	dB	30
Min. Extinction ratio at 23°C	dB	28
Min.PDL(Only for SMF on all ports)@23°C	dB	25
Max. Optical Power (CW)	mW	500
Fiber Type (Input-output)	-	Hi1060 or PMF
package dimensions	mm	$\Phi 5.5 \times 55$
Operating Temperature	°C	-5 to +70
Storage Temperature	°C	-40 to +85

\* Above specifications are for devices without connectors

\* For devices with connectors, IL will be 0.3dB higher, RL will be 5dB lower and ER will be 2dB lower

\* The PM fiber and the connector key are aligned to the slow axis

## Ordering Information

ILP	Wavelength	Pigtail Type	Fiber Type On Port 1 & 2	Fiber Length	Connector
1x1	1060nm Specify	250um bare fiber 900um loose tube Specify	PMF—PMF SMF—PMF SMF—SMF Specify	0.5m 1m 1.5m 2m Specify	N=None FC/APC FC/UPC SC/APC SC/UPC LC/UPC Specify